

Smart Measurement With The Adem®-PTZ-r

Romet is pleased to offer the Adem® in the new remote mount and instrument-drive mount configuration. With the ability to account for temperature, pressure and supercompressibility, as well as having a nominal battery life of 15 years, the Adem-PTZ-r makes an ideal upgrade to any system requiring instrumentation. The Adem-PTZ-r has a compact, rugged, service-free, tamperproof and weather resistant design with a high level of accuracy and customization.



Remote Mount Adem-PTZ-r

As a remote mount model, the Adem-PTZ-r provides the same ease of use and enhanced user experience as the tried-and-true Adem-PTZ, but also can function as a pressure and temperature recorder to monitor local gas distribution and to electronically monitor pressure and temperature in the gas distribution and transmission grid.



Romet Adem[®]-PTZ-r

Romet offers a full line of mounting brackets for the installation of an AMI-AMR device of your choice. Our custom solutions can be easily field installed or mounted and programmed at our factory to reduce installation costs and improve reliability.



Specification

- Compatible with any meter with Standard Dry Contact Pulse output
- 15 years nominal battery life
- Battery life indicated in months or percentages
- End of battery life warning
- Long lasting lithium battery
- Non-volatile EEPROM memory with full audit trail
- 3000 records (expandable to 6000) of hourly readings for 10 audit trail parameters
- 1024 daily logs
- 100 alarm logs (expandable to 200) stamped with date and time
- 166 event logs (expandable to 400)
- Live or fixed temperature and pressure compensation
- Fixed pressure factor (customizable)
- Total accuracy (nominal): +/- 0.3% of reading
- Standard ambient and gas temperature:
 - -40F to +158F (-40C to +70C)
- Four output pulses available:
 - Two isolated volume pulse output channels (corrected and uncorrected)
 - One isolated pulse output for alarm or volume (corrected or uncorrected)
 - Additional isolated corrected pulse output channel for AMR/AMI devices
- Customizable pulse width and pulse spacing
- Serial communication port - RS232 or RS485
- Analog and cellular modem compatible
- Modbus protocol available
- Optional portable keyboard
- Highly sensitive RTD sensor
- Fixed/configurable parameters with multiple levels of security
- Compatible with Itron, Sensus, Aclara, and other AMI/AMR devices
- Standard sensor ranges 0-200 PSIG and 10-190 PSIA (other pressure ranges available on request)
- Rugged single scroll button with up to 15 display parameters
- Large, easy to read LCD: 8 digits, 14 segment semi alpha-numeric
- UV resistant engineered polycarbonate enclosure
- Electronics sealed in silicon potting material for improved reliability and product life
- Weather resistant
- Nominal 12 year calibration
 - 1 point temperature calibration
 - 3 point pressure calibration

Adem-PTZ-r Approvals/Certifications

- Intrinsically safe Class 1 Division 1 & 2, Group D
- CSA Approval 2277666
- ATEX Approval FTZU 08 ATEX Q 004 & FTZU 05 ATEX 0274X (Pending)
- IECEx Certification of Conformity - 60079 Intrinsic Safety (Pending)
- MID Approval SK 17- QD- SMU-017 & SK 13- MI002- SMU005
- Third party qualification testing - Gas Technology Institute
- CE Declaration of Conformity
- Measurement Canada (Pending)

ROMET[®]
Innovate. Lead. Transform.

GAS METERS AND ELECTRONIC INSTRUMENTS

Phone 905-624-1591 USA 1-800-387-3201

www.rometlimited.com • email: romet@rometlimited.com

The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked. However, Romet Limited will not assume responsibility for any possible omissions or errors.

ROMET and ROMET & DESIGN are registered trademarks of Romet Limited. Romet Limited's gas metering technology is protected under U.S. Patent No. 4,910,519 and 6,453,721 and Canadian Patent No. 1,293,568.