




AdEM




STDID / DCID



STD CTR
END INDEX



STD CTR
SIDE INDEX



Note: AMI/AMR adaptors available upon request.

METER SIZE	ANSI 125 FF FLANGE	A	B	C	D1	D2	D3	D4	E1	WEIGHT (lbs)
RM56000	8"	16.00"	11.25"	14.87"	32.83"	34.31"	35.09"	36.03"	4.00"	189


IMPERIAL RM56000 8" FLANGE CONNECTION TECHNICAL SPECIFICATION

Connection (Flanged)	ANSI 125 FF	8"
MAOP	(psig)	175
Flow Capacity	(cfh)	56000
Rangeability* (up to 1:160 @ atmospheric condition)		1:160
Start Rate	(cfh)	26.0
Stop Rate	(cfh)	16.0
Differential @ 100 % Flow [AIR/N.G.]	(I.W.C.)	3.60
Instrument Drive Rate	(cf/rev)	100/1000
LF Pulser (Optional)	(cf/pulse)	100/1000

*Note: It should be noted, that moving parts in the meters with a greater rangeability ratio are made to high class accuracy and tight tolerances. Improper installation, stresses on piping system due to temperature changes, settling and gas conditions can create a risk of meter rejection.

CORRECTED FLOW CAPACITY AND TYPICAL ACCURACY GUIDE

RM56000 METER (SCFH)	
Gauge Pressure P.S.I.G 0.25	RM56000 Q _{max} = 56000ft ³ /hr
2	58547
5	73754
10	92763
15	111772
20	130781
25	149790
50	244834
75	339878
100	434922
125	529966
150	625010
175	720054



ROMET[®]
Innovate. Lead. Transform.

GAS METERS AND ELECTRONIC INSTRUMENTS
Phone 905-624-1591 USA 1-800-387-3201
www.rometlimited.com • email: romet@rometlimited.com

The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked. However, Romet Limited will not assume responsibility for any possible omissions or errors.

ROMET and ROMET & DESIGN are registered trademarks of Romet Limited. Romet Limited's gas metering technology is protected under U.S. Patent No. 4,910,519 and 6,453,721 and Canadian Patent No. 1,293,568.